

SMARTFEED M-4 je dodavač žice za robotsko MIG-MAG zavarivanje, dizajniran za učinkovit rad s većinom robotskih ruku na tržištu. U stanju je maksimalno povećati brzinu ruke i njenu orijentaciju zahvaljujući svojoj maloj veličini i maloj težini.



Aluminijska šasija

Utičnica senzora na kraju žice

Četiri ručne kontrole za maksimalnu kontrolu:

 Žica inča naprijed

 Žica inča obrnuto

 GAS Pročišćavanje plinom

 AIR Udar zraka


Digitalna komunikacijska utičnica



Priključak senzora sudara

10-pinska utičnica koja omogućuje pristup do četiri dodatna ulaza, kao i četiri dodatna izlaza za još više opcija PLC-a

Euro konektor utičnica



- Motorizirani pogon s četiri pogonska valjka za precizno dodavanje žice između 0,6 do 1,2 mm
- DC 48 V motor, max. brzina: 25m/min (984 IPM)
- Nije potreban alat za promjenu kalema



Isporučka s 2 konektora žice - 3 kontakta



KOMPATIBILNI IZVORI NAPAJANJA

- NEOPULSE 320 C (062474)
- NEOPULSE 400 CW (062061)
- NEOPULSE 400 G (014497)
- NEOPULSE 500 G (014503)

IZBORNI DODACI




Robotski MIG spojni kabeli
- voda






4 m	8 m	12 m
95 mm ²		
073517	069725	078581



Kompleti za robotsku
montažu dodavača
žice



Komplet za pričvršćivanje
spojnog kabela
075429

III		Prikladne žice						Isporučuje se kao standard		EN60974-5 (40°C)	IP	
U ₁₁	U ₁₂	Ne hrdajući Čelik	Alu.	CuSi CuAl	Žice s punjenom jezgrom	Elektronička Kontrolirati	m/min		Tip			mm/kg
48 V 2 A	24 V 1 A	0,6 → 1,6	0,8 → 1,6	0,8 → 1,2	0,9 → 2,4	 115 W	1 → 25	1.0 1.2	F 061873	500 A @ 60% 460 A pri 100%	21	244 x 207 x 152 / 4.5